

Робочий тиск: 6 бар



Тип	Модель	Габарити, мм.			Підключення	Площа теплообмінника, м <sup>2</sup>		Ціна, €				
		Висота, мм.	Діаметр бака, мм.	Діаметр з ізоляцією, мм.		нижній	верхній	Тепловий акумулятор	Бак з ізоляцією			
									PL/PVC	PU/PVC	PL/ABS	PS/ABS
 ВТН-1	400	1780	600	780	G 1"	1,48	1,00	2475	2635	2690	2700	2710
	500	2030	600	780	G 1"	1,84	1,00	2705	2875	2945	2955	2985
	750	2070	750	930	G 1¼"	2,42	1,40	3140	3330	3400	3420	3460
	1000	2110	850	1030	G 1¼"	3,00	2,00	4290	4495	4565	4605	4650
	1500	2240	1000	1180	G 1½"	4,10	2,82	5735	6020	6085	6135	6190
 ВТН-2	400	1780	600	780	G 1"	1,48		2290	2450	2505	2515	2525
	500	2030	600	780	G 1"	1,84		2525	2695	2765	2775	2805
	750	2070	750	930	G 1¼"	2,42		2920	3110	3180	3200	3240
	1000	2110	850	1030	G 1¼"	3,00		3880	4085	4155	4195	4240
	1500	2240	1000	1180	G 1½"	4,10		5155	5440	5505	5555	5610
 ВТН-2-ПЛЮС	400	1780	600	780	G 1"	3,85		2725	2885	2940	2950	2960
	500	2030	600	780	G 1"	4,10		2935	3105	3175	3185	3215
	750	2070	750	930	G 1¼"	4,64		3380	3570	3640	3660	3700
	1000	2110	850	1030	G 1¼"	5,10		4315	4520	4590	4630	4675
	1500	2240	1000	1180	G 1½"	6,35		5620	5905	5970	6020	6075
 ВТН-3	400	1780	600	780	G 1"			2020	2180	2235	2245	2255
	500	2030	600	780	G 1"			2190	2360	2430	2440	2470
	750	2070	750	930	G 1¼"			2530	2720	2790	2810	2850
	1000	2110	850	1030	G 1¼"			3265	3470	3540	3580	3625
	1500	2240	1000	1180	G 1½"			4310	4595	4660	4710	4765
	2000	2290	1200	1380	G 1½"			5100	5430	5545	5580	5630
	3000	2410	1400	1580	G 1½"			6970	7360	7470	7580	7595