

Робочий тиск: 3 бар



Тип	Модель	Габарити, мм.			Підключення	Площа теплообмінника, м <sup>2</sup>		Ціна, €					
		Висота, мм.	Діаметр бака, мм.	Діаметр з ізоляцією, мм.		нижній	верхній	Тепловий акумулятор	Бак з ізоляцією				
									PL/PVC	PU/PVC	PL/ABS	PS/ABS	
ВТА-1 	400	1690	600	780	G 1½"	1,5	1,40	970	1130	1185	1195	1205	
	500	1950	600	780	G 1½"	1,5	1,40	995	1165	1235	1245	1275	
							2,20	1165	1335	1405	1415	1445	
	750	1990	750	930	G 1½"	1,5	1,55	1145	1335	1405	1425	1465	
							2,10	1245	1435	1505	1525	1565	
							3,10	1430	1620	1690	1710	1750	
							3,80	1565	1755	1825	1845	1885	
	1000	2050	850*	1030	G 1½"	1,8	1,55	1380	1585	1655	1695	1740	
							2,30	1565	1770	1840	1880	1925	
							3,10	1755	1960	2030	2070	2115	
							4,60	2120	2325	2395	2435	2480	
	1500	2150	1000	1180	G 1½"	2,3	1,90	1690	1975	2040	2090	2145	
							2,90	1930	2215	2280	2330	2385	
							3,85	2160	2445	2510	2560	2615	
							4,80	2390	2675	2740	2790	2845	
	2000	2250	1200	1380	G 1½"	2,3	2,30	2115	2445	2560	2595	2645	
3,45							2355	2685	2800	2835	2885		
4,56							2585	2915	3030	3065	3115		
5,70							2830	3160	3275	3310	3360		
6,90	3075	3405	3520	3555	3605	2,3	2,30	2115	2445	2560	2595	2645	
							3,45	2355	2685	2800	2835	2885	
							4,56	2585	2915	3030	3065	3115	
							5,70	2830	3160	3275	3310	3360	
							6,90	3075	3405	3520	3555	3605	
							6,90	3075	3405	3520	3555	3605	
ВТА-1 ПЛЮС 	400	1690	600	780	G 1½"	1,5	2,00	1330	1490	1545	1555	1565	
	500	1950	600	780	G 1½"	1,5	2,85	1495	1665	1735	1745	1775	
	750	1990	750	930	G 1½"	1,5	4,45	1860	2050	2120	2140	2180	
	1000	2050	850*	1030	G 1½"	1,8	5,10	2410	2615	2685	2725	2770	
	1500	2150	1000	1180	G 1½"	2,3	6,20	2835	3120	3185	3235	3290	
	2000	2250	1200	1380	G 1½"	2,3	6,20	3090	3420	3535	3570	3620	
ВТА-2 	400	1690	600	780	G 1½"		1,40	805	965	1020	1030	1040	
	500	1950	600	780	G 1½"		1,40	830	1000	1070	1080	1110	
							2,20	1000	1170	1240	1250	1280	
							1,55	980	1170	1240	1260	1300	
	750	1990	750	930	G 1½"		2,10	1080	1270	1340	1360	1400	
							3,10	1265	1455	1525	1545	1585	
							3,80	1400	1590	1660	1680	1720	
							1,55	1170	1375	1445	1485	1530	
	1000	2050	850*	1030	G 1½"		2,30	1355	1560	1630	1670	1715	
							3,10	1545	1750	1820	1860	1905	
							3,90	1745	1950	2020	2060	2105	
							4,60	1915	2120	2190	2230	2275	
	1500	2150	1000	1180	G 1½"		1,90	1420	1705	1770	1820	1875	
							2,90	1665	1950	2015	2065	2120	
							3,85	1895	2180	2245	2295	2350	
							4,80	2125	2410	2475	2525	2580	
2000	2250	1200	1380	G 1½"		5,70	2345	2630	2695	2745	2800		
						2,30	1850	2180	2295	2330	2380		
						3,45	2090	2420	2535	2570	2620		
						4,56	2320	2650	2765	2800	2850		
5,70	2565	2895	3010	3045	3095	2,3	5,70	2565	2895	3010	3045	3095	
							6,90	2810	3140	3255	3290	3340	
ВТА-3 	400	1690	600	780	G 1½"	1,5		665	825	880	890	900	
	500	1950	600	780	G 1½"	1,5		695	865	935	945	975	
	750	1990	750	930	G 1½"	1,5		855	1045	1115	1135	1175	
	1000	2050	850*	1030	G 1½"	1,8		1005	1210	1280	1320	1365	
	1500	2150	1000	1180	G 1½"	2,3		1225	1510	1575	1625	1680	
	2000	2250	1200	1380	G 1½"	2,3		1635	1965	2080	2115	2165	

Робочий тиск: 3 бар



Тип	Модель	Габарити, мм			Підключення	Площа теплообмінника, м²		Ціна, €				
		Висота, мм.	Діаметр бака, мм.	Діаметр з ізоляцією, мм.		нижній	верхній	Тепловий акумулятор	Бак з ізоляцією			
									PL/PVC	PU/PVC	PL/ABS	PS/ABS
<p>ВТА-4</p>	200	1310	500	680	G 1½"			415	530	560	585	610
	300	1920	500	680	G 1½"			455	605	645	680	690
	400	1690	600	780	G 1½"			500	660	715	725	735
	500	1950	600	780	G 1½"			530	700	770	780	810
	750	1990	750	930	G 1½"			690	880	950	970	1010
	1000	2050	850*	1030	G 1½"			795	1000	1070	1110	1155
	1500	2150	1000	1180	G 1½"			965	1250	1315	1365	1420
	2000	2250	1200	1380	G 1½"			1370	1700	1815	1850	1900
	3000	2340	1400	1580	G 2"			2030	2420	2530	2640	2655
	4000	2400	1600	1780	G 2"			3055	3470	3605	3710	3760
	5000	2900	1600	1780	G 2"			3450	4025	4180	4290	4305
<p>ВТА-4-ЕКОНОМ</p>	100	1010	400	580	G 1"			230	325	350	380	405
	200	1310	500	680	G 1½"			340	455	485	510	535
	300	1920	500	680	G 1½"			385	535	575	610	620
	400	1655	600	780	G 1½"			425	585	640	650	660
	500	1905	600	780	G 1½"			445	615	685	695	725
	750	2005	750	930	G 1½"			595	785	855	875	915
	1000	2005	850*	1030	G 1½"			695	900	970	1010	1055
	1500	2065	1000	1180	G 1½"			915	1200	1265	1315	1370
	2000	2120	1200	1380	G 1½"			1330	1660	1775	1810	1860
	3000	2340	1400	1580	G 2"			1980	2370	2480	2590	2605
	4000	2400	1600	1780	G 2"			2960	3375	3510	3615	3665
	5000	2900	1600	1780	G 2"			3355	3930	4085	4195	4210